

PUR 68 W

Wall mounted cooker hood

with EasySwitch light-touch switches for convenient operation and LED lighting



- Powerful – 650 m³/h in Booster level
- Efficient filtration- 10-ply stainless-steel grease filter
- Safe and easy to clean – Miele CleanCover
- Suitable for every home – for extraction or recirculation



EAN: 4002515792971 / Material number: 10565920 /
Old Material Number: 28416854GB

General information	
Model identifier	PUR 68 W
Manufacturer material number	10565920
EAN number	4002515792971
Marketing class	Silver
Construction type	
Wall mounted cooker hood	•
Construction type and design	
Colour	Stainless steel
Operating modes	
Type of air guide	Can be retrofitted
Recirculation conversion kit (order separately)	DUW 20
Active charcoal filter (order separately)	DKF 12-P
Design	
Possible in RAL colour (specify colour code when ordering)	•
User convenience	
Electronic controls	•
Controls	Light-touch switches with LEDs
Power levels (number without Booster level)	3
Booster levels	1
Easy-to-clean canopy interior – CleanCover	•
Efficiency	
Energy efficiency class (A+++ – D)	A
Annual energy consumption in kWh/year	47.0
Fluid dynamic efficiency class	A
Lighting efficiency class	A
Grease filtering efficiency class	A
Filter system	
Number of dishwasher-safe stainless steel grease filters (10-ply)	2
Lighting	
Number x W	2 x 3 W
Light intensity in lx	330 lx
Colour temperature in K	3000 Kelvin
Fan	
Dual-action blower	•
Exhaust air	
Air throughput in Level 1 (m ³ /h) according to EN 61591	265
Air throughput in Level 2 (m ³ /h) according to EN 61591	320
Air throughput in Level 3 (m ³ /h) according to EN 61591	395
Air throughput in Booster level 1 (m ³ /h) according to EN 61591	650
Sound power in Level 1 (dB(A) re 1 pW) according to EN 60704-3	47.0
Sound power in Level 2 (dB(A) re 1 pW) according to EN 60704-3	52.0
Sound power in Level 3 (dB(A) re 1 pW) according to EN 60704-3	56.0

PUR 68 W

Wall mounted cooker hood

with EasySwitch light-touch switches for convenient operation and LED lighting



EAN: 4002515792971 / Material number: 10565920 /
Old Material Number: 28416854GB

Sound power in Booster level 1 (dB(A) re 1 pW) acc. to EN 60704-3	67.0
-------------------------------------------------------------------	------

Sound pressure in Level 1 (dB(A) re 20 µPa) according to EN 60704-2-13	32.0
------------------------------------------------------------------------	------

Sound pressure in Level 2 (dB(A) re 20 µPa) according to EN 60704-2-13	37.0
------------------------------------------------------------------------	------

Sound pressure in Level 3 (dB(A) re 20 µPa) according to EN 60704-2-13	41.0
------------------------------------------------------------------------	------

Sound pressure in Booster level 1 (dB(A) re 20 µPa) acc. to EN 60704-2-13	52.0
---------------------------------------------------------------------------	------

Recirculation

Air throughput in Level 1 (m³/h) according to EN 61591	190
--------------------------------------------------------	-----

Air throughput in Level 2 (m³/h) according to EN 61591	270
--------------------------------------------------------	-----

Air throughput in Level 3 (m³/h) according to EN 61591	330
--------------------------------------------------------	-----

Air throughput in Booster level 1 (m³/h) according to EN 61591	460
----------------------------------------------------------------	-----

Sound power in Level 1 (dB(A) re 1 pW) according to EN 60704-3	54.0
----------------------------------------------------------------	------

Sound power in Level 2 (dB(A) re 1 pW) according to EN 60704-3	60.0
----------------------------------------------------------------	------

Sound power in Level 3 (dB(A) re 1 pW) according to EN 60704-3	64.0
----------------------------------------------------------------	------

Sound power in Booster level 1 (dB(A) re 1 pW) acc. to EN 60704-3	71.0
-------------------------------------------------------------------	------

Sound pressure in Level 1 (dB(A) re 20 µPa) according to EN 60704-2-13	39.0
------------------------------------------------------------------------	------

Sound pressure in Level 2 (dB(A) re 20 µPa) according to EN 60704-2-13	45.0
------------------------------------------------------------------------	------

Sound pressure in Level 3 (dB(A) re 20 µPa) according to EN 60704-2-13	48.0
------------------------------------------------------------------------	------

Sound pressure in Booster level 1 (dB(A) re 20 µPa) acc. to EN 60704-2-13	56.0
---------------------------------------------------------------------------	------

Safety

Safety switch-off	•
-------------------	---

Technical data

Canopy width in mm	598
--------------------	-----

Overall hood height for extraction mode and external in mm	685–1005
------------------------------------------------------------	----------

Overall height for recirculation mode cooker hoods in mm	815–1135
----------------------------------------------------------	----------

Overall height for vented and external in in. (mm)	685
----------------------------------------------------	-----

Overall height for extraction mode and external mode cooker hoods in mm	1005
-------------------------------------------------------------------------	------

Canopy height in mm	62
---------------------	----

Overall height for recirculation in in. (mm)	815
----------------------------------------------	-----

Canopy depth in mm	500
--------------------	-----

Overall height for recirculation mode cooker hoods in mm	1135
----------------------------------------------------------	------

Net weight in kg	21.0
------------------	------

Length of supply lead in m	1.5
----------------------------	-----

Standard plug fitted	•
----------------------	---

Minimum height above electric hobs in mm	450
------------------------------------------	-----

Minimum safety distance above gas hobs (max. 12.6 kW total power, burner ≤ 4.5 kW) in mm	650
------------------------------------------------------------------------------------------	-----

PUR 68 W

Wall mounted cooker hood

with EasySwitch light-touch switches for convenient operation and LED lighting



EAN: 4002515792971 / Material number: 10565920 /
Old Material Number: 28416854GB

Number of phases	1
Total rated load in kW	0.22
Voltage in V	230
Fuse rating in A	10
Frequency in Hz	50

Installation notes

Extraction ducting connection at top	•
Diameter of exhaust duct in mm	150
Telescopic chimney	•

Accessories included

Non-return flap	•
-----------------	---

