

DA 2668

Extractor unit

with energy-efficient LED lighting and light-touch switches for easy use.



- Customised kitchen design – fully integrated in 580 mm width
- Unique user convenience – Con@ctivity
- Powerful – 585 m<sup>3</sup>/h in Booster level
- Energy-efficient and quiet – powerful ECO motor
- Efficient filtration- 10-ply stainless-steel grease filter



EAN: 4002516001522 / Material number: 10851380 /  
Old Material Number: 28266855GB

General information	
Model identifier	DA 2668
Manufacturer material number	10851380
EAN number	4002516001522
Marketing class	Platinum
Construction type	
Integrated extractor	•
Construction type and design	
Colour	Stainless steel
Operating modes	
Type of air guide	Can be retrofitted
Recirculation conversion kit (order separately)	DUU 151
Active charcoal filter (order separately)	DKF 19-P
Design	
Edge extraction	•
User convenience	
Miele@home	•
Electronic controls	•
Con@ctivity	Yes
Controls	Light-touch switches with LEDs
Miele@mobile app	•
Power levels (number without Booster level)	3
Run-on time 5/15 min.	•
Booster levels	1
Grease filter saturation indicator	•
Active charcoal filter saturation indicator	•
Easy-to-clean canopy interior – CleanCover	•
Efficiency	
Energy efficiency class (A+++ – D)	A+
ECO motor (DC motor)	•
PowerManagement system	•
Annual energy consumption in kWh/year	28.4
Fluid dynamic efficiency class	A
Lighting efficiency class	A
Grease filtering efficiency class	A
Filter system	
Number of dishwasher-safe stainless steel grease filters (10-ply)	2
Lighting	
Number x W	2 x 4,5 W
Light intensity in lx	700 lx
Colour temperature in K	3500 Kelvin
Dimmer function	•
Fan	
Dual-action blower	•
Exhaust air	
Air throughput in Level 1 (m <sup>3</sup> /h) according to EN 61591	175

DA 2668

Extractor unit

with energy-efficient LED lighting and light-touch switches for easy use.



EAN: 4002516001522 / Material number: 10851380 /  
Old Material Number: 28266855GB

Air throughput in Level 2 (m <sup>3</sup> /h) according to EN 61591	265
Air throughput in Level 3 (m <sup>3</sup> /h) according to EN 61591	365
Air throughput in Booster level 1 (m <sup>3</sup> /h) according to EN 61591	585
Sound power in Level 1 (dB(A) re 1 pW) according to EN 60704-3	35.0
Sound power in Level 2 (dB(A) re 1 pW) according to EN 60704-3	44.0
Sound power in Level 3 (dB(A) re 1 pW) according to EN 60704-3	51.0
Sound power in Booster level 1 (dB(A) re 1 pW) acc. to EN 60704-3	64.0
Sound pressure in Level 1 (dB(A) re 20 µPa) according to EN 60704-2-13	21.0
Sound pressure in Level 2 (dB(A) re 20 µPa) according to EN 60704-2-13	29.0
Sound pressure in Level 3 (dB(A) re 20 µPa) according to EN 60704-2-13	37.0
Sound pressure in Booster level 1 (dB(A) re 20 µPa) acc. to EN 60704-2-13	50.0
<b>Recirculation</b>	
Air throughput in Level 1 (m <sup>3</sup> /h) according to EN 61591	115
Air throughput in Level 2 (m <sup>3</sup> /h) according to EN 61591	200
Air throughput in Level 3 (m <sup>3</sup> /h) according to EN 61591	330
Air throughput in Booster level 1 (m <sup>3</sup> /h) according to EN 61591	490
Sound power in Level 1 (dB(A) re 1 pW) according to EN 60704-3	46.0
Sound power in Level 2 (dB(A) re 1 pW) according to EN 60704-3	56.0
Sound power in Level 3 (dB(A) re 1 pW) according to EN 60704-3	64.0
Sound power in Booster level 1 (dB(A) re 1 pW) acc. to EN 60704-3	74.0
Sound pressure in Level 1 (dB(A) re 20 µPa) according to EN 60704-2-13	32.0
Sound pressure in Level 2 (dB(A) re 20 µPa) according to EN 60704-2-13	42.0
Sound pressure in Level 3 (dB(A) re 20 µPa) according to EN 60704-2-13	49.0
Sound pressure in Booster level 1 (dB(A) re 20 µPa) acc. to EN 60704-2-13	60.0
<b>Safety</b>	
Safety switch-off	•
<b>Technical data</b>	
Canopy width in mm	580
Canopy height in mm	63
Canopy depth in mm	293
Net weight in kg	12.0
Length of supply lead in m	1.5
Standard plug fitted	•
Minimum height above electric hobs in mm	450

DA 2668

Extractor unit

with energy-efficient LED lighting and light-touch switches for easy use.



EAN: 4002516001522 / Material number: 10851380 /  
Old Material Number: 28266855GB

Minimum safety distance above gas hobs (max. 12.6 kW  
total power, burner  $\leq$  4.5 kW) in mm

Number of phases	1
Total rated load in kW	0.08
Voltage in V	230
Fuse rating in A	10
Frequency in Hz	50

#### Installation notes

Extraction ducting connection at top	•
Diameter of exhaust duct in mm	150
Combination with WiFi-enabled Miele hob	recommended

#### Accessories included

Non-return flap	•
-----------------	---