

DA 6698 W Purist. Ed.6000

Wall mounted cooker hood

with energy-efficient LED lighting and touch controls for simple operation.



- Family design – based on Miele built-in appliances
- Unique user convenience – Con@ctivity
- Powerful – 640 m³/h in Booster level
- Energy-efficient and quiet – powerful ECO motor
- Pleasantly quiet – Miele Silence package



EAN: 4002516585770 / Material number: 12050600 /
Old Material Number: 28669841GB

| General information | |
|---|---------------------------|
| Model identifier | DA 6698 W Purist. Ed.6000 |
| Manufacturer material number | 12050600 |
| EAN number | 4002516585770 |
| Marketing class | Diamond |
| Construction type | |
| Wall mounted cooker hood | • |
| Construction type and design | |
| Colour | Obsidian black |
| Operating modes | |
| Type of air guide | Can be retrofitted |
| User convenience | |
| Electronic controls | • |
| Con@ctivity | Yes |
| Booster levels | 1 |
| Silence package | • |
| Efficiency | |
| Energy efficiency class (A+++ – D) | A++ |
| ECO motor (DC motor) | • |
| PowerManagement system | • |
| Annual energy consumption in kWh/year | 24.6 |
| Fluid dynamic efficiency class | A |
| Lighting efficiency class | A |
| Grease filtering efficiency class | A |
| Filter system | |
| Number of dishwasher-safe stainless steel grease filters (10-ply) | 3 |
| Lighting | |
| Number x W | 3 x 3 W |
| Light intensity in lx | 670 lx |
| Colour temperature in K | 3500 Kelvin |
| Fan | |
| Dual-action blower | • |
| Exhaust air | |
| Air throughput in Level 1 (m ³ /h) according to EN 61591 | 200 |
| Air throughput in Level 2 (m ³ /h) according to EN 61591 | 300 |
| Air throughput in Level 3 (m ³ /h) according to EN 61591 | 400 |
| Air throughput in Booster level 1 (m ³ /h) according to EN 61591 | 640 |
| Sound power in Level 1 (dB(A) re 1 pW) according to EN 60704-3 | 36.0 |
| Sound power in Level 2 (dB(A) re 1 pW) according to EN 60704-3 | 44.0 |
| Sound power in Level 3 (dB(A) re 1 pW) according to EN 60704-3 | 52.0 |
| Sound power in Booster level 1 (dB(A) re 1 pW) acc. to EN 60704-3 | 63.0 |

DA 6698 W Purist. Ed.6000

Wall mounted cooker hood

with energy-efficient LED lighting and touch controls for simple operation.



EAN: 4002516585770 / Material number: 12050600 /
Old Material Number: 28669841GB

| | |
|--|----------|
| Sound pressure in Level 1 (dB(A) re 20 µPa) according to EN 60704-2-13 | 21.0 |
| Sound pressure in Level 2 (dB(A) re 20 µPa) according to EN 60704-2-13 | 29.0 |
| Sound pressure in Level 3 (dB(A) re 20 µPa) according to EN 60704-2-13 | 37.0 |
| Sound pressure in Booster level 1 (dB(A) re 20 µPa) acc. to EN 60704-2-13 | 48.0 |
| Recirculation | |
| Air throughput in Level 1 (m ³ /h) according to EN 61591 | 110 |
| Air throughput in Level 2 (m ³ /h) according to EN 61591 | 185 |
| Air throughput in Level 3 (m ³ /h) according to EN 61591 | 315 |
| Air throughput in Booster level 1 (m ³ /h) according to EN 61591 | 460 |
| Sound power in Level 1 (dB(A) re 1 pW) according to EN 60704-3 | 45.0 |
| Sound power in Level 2 (dB(A) re 1 pW) according to EN 60704-3 | 53.0 |
| Sound power in Level 3 (dB(A) re 1 pW) according to EN 60704-3 | 63.0 |
| Sound power in Booster level 1 (dB(A) re 1 pW) acc. to EN 60704-3 | 72.0 |
| Sound pressure in Level 1 (dB(A) re 20 µPa) according to EN 60704-2-13 | 30.0 |
| Sound pressure in Level 2 (dB(A) re 20 µPa) according to EN 60704-2-13 | 38.0 |
| Sound pressure in Level 3 (dB(A) re 20 µPa) according to EN 60704-2-13 | 48.0 |
| Sound pressure in Booster level 1 (dB(A) re 20 µPa) acc. to EN 60704-2-13 | 57.0 |
| Safety | |
| Safety switch-off | • |
| Single-ply safety glass (ESG) | • |
| Technical data | |
| Canopy width in mm | 898 |
| Overall hood height for extraction mode and external in mm | 710–1030 |
| Overall height for recirculation mode cooker hoods in mm | 840–1160 |
| Overall height for vented and external in in. (mm) | 710 |
| Overall height for extraction mode and external mode cooker hoods in mm | 1030 |
| Canopy height in mm | 85 |
| Overall height for recirculation in in. (mm) | 840 |
| Canopy depth in mm | 500 |
| Overall height for recirculation mode cooker hoods in mm | 1160 |
| Net weight in kg | 26.0 |
| Length of supply lead in m | 1.5 |
| Standard plug fitted | • |
| Minimum height above electric hobs in mm | 450 |
| Minimum safety distance above gas hobs (max. 12.6 kW total power, burner ≤ 4.5 kW) in mm | 650 |
| Number of phases | 1 |

DA 6698 W Purist. Ed.6000

Wall mounted cooker hood

with energy-efficient LED lighting and touch controls for simple operation.



EAN: 4002516585770 / Material number: 12050600 /
Old Material Number: 28669841GB

| | |
|------------------------|------|
| Total rated load in kW | 0.08 |
| Voltage in V | 230 |
| Fuse rating in A | 10 |
| Frequency in Hz | 50 |

Installation notes

| | |
|--------------------------------------|-----|
| Extraction ducting connection at top | • |
| Diameter of exhaust duct in mm | 150 |
| Telescopic chimney | • |

Accessories included

| | |
|-----------------|---|
| Non-return flap | • |
|-----------------|---|