

PUR 98 D

Island cooker hood

with energy-efficient LED lighting and light-touch switches for easy use.



- Timeless design – stainless steel canopy 898 mm wide
- Powerful – 650 m³/h in Booster level
- Efficient filtration- 10-ply stainless-steel grease filter
- Safe and easy to clean – Miele CleanCover
- Suitable for every home – for extraction or recirculation



EAN: 4002516585794 / Material number: 12050650 /
Old Material Number: 28410858GB

General information	
Model identifier	PUR 98 D
Manufacturer material number	12050650
EAN number	4002516585794
Marketing class	Silver
Construction type	
Island cooker hood	•
Construction type and design	
Colour	Stainless steel
Operating modes	
Type of air guide	Can be retrofitted
User convenience	
Electronic controls	•
Booster levels	1
Efficiency	
Energy efficiency class (A+++ – D)	A
Annual energy consumption in kWh/year	51.8
Fluid dynamic efficiency class	A
Lighting efficiency class	A
Grease filtering efficiency class	A
Filter system	
Number of dishwasher-safe stainless steel grease filters (10-ply)	3
Lighting	
Number x W	4 x 3 W
Light intensity in lx	500 lx
Colour temperature in K	3000 Kelvin
Fan	
Dual-action blower	•
Exhaust air	
Air throughput in Level 1 (m ³ /h) according to EN 61591	280
Air throughput in Level 2 (m ³ /h) according to EN 61591	330
Air throughput in Level 3 (m ³ /h) according to EN 61591	400
Air throughput in Booster level 1 (m ³ /h) according to EN 61591	650
Sound power in Level 1 (dB(A) re 1 pW) according to EN 60704-3	48.0
Sound power in Level 2 (dB(A) re 1 pW) according to EN 60704-3	53.0
Sound power in Level 3 (dB(A) re 1 pW) according to EN 60704-3	57.0
Sound power in Booster level 1 (dB(A) re 1 pW) acc. to EN 60704-3	69.0
Sound pressure in Level 1 (dB(A) re 20 µPa) according to EN 60704-2-13	31.0
Sound pressure in Level 2 (dB(A) re 20 µPa) according to EN 60704-2-13	35.0
Sound pressure in Level 3 (dB(A) re 20 µPa) according to EN 60704-2-13	39.0

PUR 98 D

Island cooker hood

with energy-efficient LED lighting and light-touch switches for easy use.



EAN: 4002516585794 / Material number: 12050650 /
Old Material Number: 28410858GB

Sound pressure in Booster level 1 (dB(A) re 20 µPa) acc. to EN 60704-2-13 51.0

Recirculation

Air throughput in Level 1 (m³/h) according to EN 61591 190

Air throughput in Level 2 (m³/h) according to EN 61591 270

Air throughput in Level 3 (m³/h) according to EN 61591 330

Air throughput in Booster level 1 (m³/h) according to EN 61591 460

Sound power in Level 1 (dB(A) re 1 pW) according to EN 60704-3 57.0

Sound power in Level 2 (dB(A) re 1 pW) according to EN 60704-3 62.0

Sound power in Level 3 (dB(A) re 1 pW) according to EN 60704-3 66.0

Sound power in Booster level 1 (dB(A) re 1 pW) acc. to EN 60704-3 73.0

Sound pressure in Level 1 (dB(A) re 20 µPa) according to EN 60704-2-13 40.0

Sound pressure in Level 2 (dB(A) re 20 µPa) according to EN 60704-2-13 45.0

Sound pressure in Level 3 (dB(A) re 20 µPa) according to EN 60704-2-13 49.0

Sound pressure in Booster level 1 (dB(A) re 20 µPa) acc. to EN 60704-2-13 56.0

Safety

Safety switch-off •

Technical data

Canopy width in mm 898

Overall height for vented and external in in. (mm) 690

Overall height for extraction mode and external mode cooker hoods in mm 990

Canopy height in mm 70

Overall height for recirculation in in. (mm) 750

Canopy depth in mm 598

Overall height for recirculation mode cooker hoods in mm 1060

Net weight in kg 34.0

Hard-wired connection •

Minimum height above electric hobs in mm 450

Minimum safety distance above gas hobs (max. 12.6 kW total power, burner ≤ 4.5 kW) in mm 650

Number of phases 1

Total rated load in kW 0.23

Voltage in V 230

Fuse rating in A 10

Frequency in Hz 50

Installation notes

Extraction ducting connection at top •

Diameter of exhaust duct in mm 150

Telescopic chimney •

Accessories included

Non-return flap •

PUR 98 D

Island cooker hood

with energy-efficient LED lighting and light-touch switches for easy use.