

DAH 2960 Escala  
Wall mounted cooker hood  
with Con@ctivity and smart touch controls for convenience



- Lots of headroom – with glass canopy 898 mm wide
- Unique user convenience – Con@ctivity
- Efficient filtration- 10-ply stainless-steel grease filter
- Perfect match – glass panel and canopy in the same colour
- Suitable for every home – for extraction or recirculation



EAN: 4002516801504 / Material number: 12545640 /  
Old Material Number: 28H2960BGB

General information	
Model identifier	DAH 2960 Escala
Manufacturer material number	12545640
EAN number	4002516801504
Marketing class	Gold
Construction type	
Wall mounted cooker hood	•
Construction type and design	
Colour	Obsidian black
Operating modes	
Type of air guide	Can be retrofitted
Active charcoal filter (order separately)	DKF 29
Design	
Edge extraction	•
User convenience	
Miele@home	•
Electronic controls	•
Con@ctivity	Yes
Touch-on-glass controls	•
Controls	ComfortControl
ON/OFF switch	•
Power levels (number without Booster level)	3
Booster levels	1
Easy-to-clean canopy interior – CleanCover	•
Efficiency	
Energy efficiency class (A+++ – D)	B
Annual energy consumption in kWh/year	72.3
Fluid dynamic efficiency class	B
Lighting efficiency class	A
Grease filtering efficiency class	D
Filter system	
Number of dishwasher-safe stainless steel grease filters (10-ply)	2
Lighting	
Number x W	1 x 3,2 W
Light intensity in lx	300 lx
Colour temperature in K	3500 Kelvin
Fan	
Dual-action blower	•
Exhaust air	
Air throughput in Level 1 (m <sup>3</sup> /h) according to EN 61591	215
Air throughput in Level 2 (m <sup>3</sup> /h) according to EN 61591	315
Air throughput in Level 3 (m <sup>3</sup> /h) according to EN 61591	415
Air throughput in Booster level 1 (m <sup>3</sup> /h) according to EN 61591	675
Sound power in Level 1 (dB(A) re 1 pW) according to EN 60704-3	41.0
Sound power in Level 2 (dB(A) re 1 pW) according to EN 60704-3	47.0

DAH 2960 Escala  
Wall mounted cooker hood  
with Con@ctivity and smart touch controls for convenience



EAN: 4002516801504 / Material number: 12545640 /  
Old Material Number: 28H2960BGB

Sound power in Level 3 (dB(A) re 1 pW) according to EN 60704-3	53.0
Sound power in Booster level 1 (dB(A) re 1 pW) acc. to EN 60704-3	65.0
Sound pressure in Level 1 (dB(A) re 20 µPa) according to EN 60704-2-13	27.0
Sound pressure in Level 2 (dB(A) re 20 µPa) according to EN 60704-2-13	33.0
Sound pressure in Level 3 (dB(A) re 20 µPa) according to EN 60704-2-13	39.0
Sound pressure in Booster level 1 (dB(A) re 20 µPa) acc. to EN 60704-2-13	51.0
<b>Recirculation</b>	
Air throughput in Level 1 (m <sup>3</sup> /h) according to EN 61591	190
Air throughput in Level 2 (m <sup>3</sup> /h) according to EN 61591	280
Air throughput in Level 3 (m <sup>3</sup> /h) according to EN 61591	380
Air throughput in Booster level 1 (m <sup>3</sup> /h) according to EN 61591	575
Sound power in Level 1 (dB(A) re 1 pW) according to EN 60704-3	47.0
Sound power in Level 2 (dB(A) re 1 pW) according to EN 60704-3	54.0
Sound power in Level 3 (dB(A) re 1 pW) according to EN 60704-3	60.0
Sound power in Booster level 1 (dB(A) re 1 pW) acc. to EN 60704-3	71.0
Sound pressure in Level 1 (dB(A) re 20 µPa) according to EN 60704-2-13	33.0
Sound pressure in Level 2 (dB(A) re 20 µPa) according to EN 60704-2-13	40.0
Sound pressure in Level 3 (dB(A) re 20 µPa) according to EN 60704-2-13	46.0
Sound pressure in Booster level 1 (dB(A) re 20 µPa) acc. to EN 60704-2-13	57.0
<b>Safety</b>	
Safety switch-off	•
Single-ply safety glass (ESG)	•
<b>Technical data</b>	
Canopy width in mm	898
Overall hood height for extraction mode and external in mm	830–1210
Overall height for recirculation mode cooker hoods in mm	443
Overall height for vented and external in in. (mm)	830
Overall height for extraction mode and external mode cooker hoods in mm	1210
Canopy height in mm	443
Overall height for recirculation in in. (mm)	443
Canopy depth in mm	388
Overall height for recirculation mode cooker hoods in mm	443
Net weight in kg	18.0
Length of supply lead in m	1.3
Standard plug fitted	•



DAH 2960 Escala  
Wall mounted cooker hood  
with Con@ctivity and smart touch controls for convenience



EAN: 4002516801504 / Material number: 12545640 /  
Old Material Number: 28H2960BGB

Minimum height above electric hobs in mm	450
Minimum safety distance above gas hobs (max. 12.6 kW total power, burner $\leq$ 4.5 kW) in mm	650
Number of phases	1
Total rated load in kW	0.20
Voltage in V	230
Fuse rating in A	10
Frequency in Hz	50
<b>Installation notes</b>	
Extraction ducting connection at top	•
Diameter of exhaust duct in mm	150
<b>Accessories included</b>	
Non-return flap	•

DAH 2960 Escala  
Wall mounted cooker hood  
with Con@ctivity and smart touch controls for convenience



DAH2960 Installation drawings

1) Break-through if the mains connection is not made with a mains plug, but with a fixed connection., 2) Exhaust air opening  $\varnothing$  200 mm, so that the exhaust air line can be moved in the wall. Exhaust air connection  $\varnothing$  150 mm to the top or alternatively to the rear., 3) Air outlet for recirculated air. The distance to the ceiling or furniture mounted above the unit should be at least 300 mm.