

## KU 7015 D

Built-under refrigerator, 82–88 cm niche height with LED lighting and split door shelves in a compact design. Requires kitchen fronts with a minimum height of 72 cm.



- Optimum and maintenance-free LED
- Flexible inner door – split door shelves
- Dishwasher-proof door shelves – ComfortClean
- Cool food down quickly thanks to SuperCool



EAN: 4002516848738 / Material number: 12690480 /  
Old Material Number: 36701510GB

<b>General information</b>	
Model identifier	KU 7015 D
Manufacturer material number	12690480
EAN number	4002516848738
Marketing class	Silver
<b>Appliance category</b>	
Refrigerator	•
<b>Construction type</b>	
Built-in appliance	•
Integrated appliance	•
Undercounter appliance	•
Door hinge	right
Convertible door hinging	•
<b>User convenience</b>	
Fridge zone lighting	LED
Networking with Miele@home	•
ComfortClean	•
<b>Control system</b>	
Operating concept	EasyControl
SuperCool	•
No. of temperature zones	1
Sabbath mode	•
<b>Fridge/Fridge section</b>	
No. of shelves	3
Number of inner door racks for tinned food	2
Door rack for bottles	1
Door shelves	3
<b>Efficiency and sustainability</b>	
Energy efficiency class (A–G)	D
Annual energy consumption in kWh	74.10
Energy consumption in 24 h in kWh	0.20
<b>Safety</b>	
Acoustic door alarm	•
Optical door alarm	•
<b>Technical data</b>	
Niche width in mm min.	600
Niche width in mm max.	600
Niche height in mm min.	820
Niche height in mm max.	880
Niche depth in mm	560
Appliance width in mm	597
Appliance height in mm	818
Appliance depth in mm	550
Weight in kg	33.0
Door hinge technology	Fixed door
Max. door front weight – refrigerator, in kg	10
Climate range	SN-T
Refrigerator compartment in l	127

## KU 7015 D

Built-under refrigerator, 82–88 cm niche height  
with LED lighting and split door shelves in a compact design. Requires kitchen fronts with a minimum height of 72 cm.




EAN: 4002516848738 / Material number: 12690480 /  
Old Material Number: 36701510GB

Total usable capacity in l	127
Acoustic airborne noise emission class (A–D)	B
Sound emissions in dB(A) re 1 pW	34
Current consumption (mA)	2000
Voltage in V	220-240
Fuse rating in A	13
Number of phases	1
Frequency in Hz	50-60
Length of supply lead in m	2.2
Replacing lamps	Service
<b>Accessories included</b>	
Egg tray	•
Water filter	Nein

## KU 7015 D

Built-under refrigerator, 82–88 cm niche height

with LED lighting and split door shelves in a compact design. Requires kitchen fronts with a minimum height of 72 cm.



KU7016D, KU7015D, KU7035D, FNUS7040D, Built-under, side view